

# Auto Tray - 260

## Adjustable Tray Loader

Auto Tray-260 is the first adjustable auto-tray loader that can be integrated with DP automated handlers. Unlike Auto Tray-250, it is not only 2 in 1 function (tray in & tray out), but also can support more than 20 types of nonstandard trays. The dimension coverage is from 120 to 154mm width and 120 to 154mm length. Also, it is capable to load 25 trays at once to make your automated production line more efficient.



## Specifications

<b>Tray Type</b>	<b>Non-standard trays</b>
<b>Tray Capacity</b>	<b>25 trays</b>
<b>Tray Change Cycle</b>	<b>25 seconds</b>
<b>Tray Coverage</b>	<b>Width : 120~154 mm Length : 300~323mm</b>
<b>Serial Interface</b>	<b>RS232</b>
<b>Dimension (WxDxH)</b>	<b>300x1020x1100mm</b>
<b>Weight</b>	<b>50KG</b>
<b>Power Supply</b>	<b>220-240Vac, 50/60Hz</b>
<b>Air Pressure</b>	<b>0.6MPa(~6.0kg/cm<sup>2</sup>) ; ø6mm Air Pipe</b>
<b>Operating Environment</b>	<b>Temperature: 22°C±2°C Humidity: 55~65%</b>

**Taiwan Headquarter** TEL : + 886 - 2 - 2790 - 7932 FAX : + 886 - 2 - 2790 - 7916

4F, No. 7, Lane 143, Xinming Rd., Neihu District, Taipei, Taiwan, R.O.C 114

**China Office** TEL : + 86 - 21 - 5160 - 0157

Room 518, Building 66, Lane 1333, Xinlong Road, Vanke Hongqiao CBD, Min Hang District, Shanghai, P.R.C. 201101

**U.S. Office** TEL: + 1 - 909 - 274 - 8860

209 E Baseline RD, Suite E208 #8, Tempe, AZ, 85283, USA



**Dediprolog  
Technology**

Email: sales@dediprolog.com

Website: www.dediprolog.com